

LATEX-C 502

Acrylic emulsion-based additive that increases the elasticity, adherence and water impermeability of the mortar

DESCRIPTION:

Acrylic emulsion-based additive that increases the elasticity, adherence and water impermeability of the mortar it is used.

ADVANTAGES:

Prevents cracking by providing elasticity.
Increases adherence of mortar.
It increases the strength of the mortar.
Water repellent.
It prevents the capillary from absorbing water.
Used in machine plasters.
Ready to use.

USAGE AREAS:

Repair mortars.
Ceramic, tile and stone adhesives.
In coarse and fine plaster mortars.

APPLICATION METHOD:

Preparation Of The Mixture:

Enough clean water is poured into an empty and clean bucket and dosed between 5% and 20% according to the nature of the mortar to be mixed into the mortar water.
The mortar is made with the formed water.
The product must be put into the mixing water and not directly added to the mortar.

ISSUES TO BE CONSIDERED:

Temperature should be between +5 °C and +35 °C during the application.

Do not apply on surfaces that are at risk of frost.

In addition, it should not be applied in extremely hot, rainy or windy weather.

These time can change according to temperature and moist ratio.

CLEANING OF INSTRUMENTS:

DAYMAN LATEX C –502 should be cleaned by water just after the application.

CONSUME:

% 5- %20 of the total cement percentage.

PACKING:

30, 00 kg. Plastic Bin.

80x120 Pallet Dimension

24 Qty on Pallet

5, 00 kg. Plastic Bin

12 Qty on Collies

80x120 Pallet Dimension

30x12 =360 Qty on Pallet



LATEX-C 502

Acrylic emulsion-based additive that increases the elasticity, adherence and water impermeability of the mortar

COLOR:

White

SHELF LIFE:

1 year from the production date under proper storage conditions.

Opened packages should be kept tightly closed.

Store between + 5 and + 30 C to avoid frost.

Wear work clothes, protective gloves, glasses and masks should be used during application.

SAFETY RECOMMENDATIONS:

Skin and eyes should not be contacted, in case of contact with wash plenty of water and soap, if swallowed seek medical attention immediately.

Food and beverage materials should not be kept in the application area and should not be eaten.

Store out of reach of children.

This product packaging must be disposed of in accordance with applicable laws.

This responsibility is belong the end user.

For more information please check the Material Safety Data Sheet.

LIMITATIONS OF LIABILITY:

The information in this technical data sheet is given according to technical information, experience and test result.

As GENERALTÜRK A.Ş. cannot control the usage of the product that used under which kind of conditions, it does not accept any responsibility for the application result and does not guarantee it.

The product suitability for the product user should be tested and decided accordingly. All products should be considered in the advice of those technical knowledge and equipment.

GENERAL TURK A.Ş can not accept any responsibility that occurs because of miss-use, it only responsible for the written suggestions that shows the products where and how use.


GENERALTÜRK A.Ş. It may change the properties of its products without announcement.

The technical data sheet is valid until the next time it is printed and all previous technical data sheets invalidate the description / January 2020



LATEX-C 502

Acrylic emulsion-based additive that increases the elasticity, adherence and water impermeability of the mortar

 2765	
GENERALTÜRK TEKNİK YALITIM KİMYA END. SAN. TİC. A.Ş. YUNUSELİ MH. 15. YAVUZ SK. NO: 21 OSMANGAZİ - BURSA / TÜRKİYE 20	
2765 - CPR - 0156 EN 934 - 2	
LATEX-C 502	
CONCRETE ADMIXTURES	
intended use in concrete for water resisting;	
Colour	White
Heating of Application	: +5°C +30°C