

D-THERM 556

It is a water based, acrylic emulsion based exterior primer.

DESCRIPTION:

It is a water based, acrylic emulsion based exterior primer.

ADVANTAGES:

Increases ground adherence with paint to be coated on.
Balances paint consumption.
Suitable for acrylic plasters.
Excellent adhesion to mineral surfaces.
Easy to apply.
Water vapor permeable.

USAGE AREAS:

D-THERM 555 Under exterior paint,
Under D-THERM 554 - D-THERM 553,
Can be used as a primer on all acrylic based products.

TECHNICAL SPESIFICATION :

((23°C, %50 Relative Humidity)

Pre Dry (Min.) :4 Hours

Coating on Again (min) :8 hours

Application Temperature : +5°C +30°C

Color : White

*** These values are valid for the performance of the finished applications at the end of the full drying period (28 days). Due to differences in temperature

and humidity values in the construction site, the values may change.

APPLICATION METHOD:

Surface Preparation:

The surface; must be cured, dry and durable. Loose surface mortar and such as residues should be cleaned and reached durable surface.

In case of the necessity the surface should be cleaned mechanically

Oil, grease, dirt, paint, salt and vomiting that prevent adhesion should be removed.

Preparation Of The Mixture:

D-THERM - 556 is mixed with low speed mixer at 400 rpm until it reaches homogeneous consistency.

Can be thinned by water maximum 10% rate.

Application:

DAYMAN D-THERM - 556 It should be applied on the surface with roller, brush and suitable spraying equipment.

ISSUES TO BE CONSIDERED:

Temperature should be between +5 °C and +35 °C during the application.

Do not apply on surfaces that are at risk of frost.



D-THERM 556

It is a water based, acrylic emulsion based exterior primer.

In addition, it should not be applied in extremely hot, rainy or windy weather. After the application the applied area should prevent from the direct water contact in 24 hours.

CLEANING OF INSTRUMENTS:

DAYMAN D-THERM 556 should be cleaned by water when it wet.

DAYMAN D-THERM 556 after become dry should be cleaned by the mechanical ways.

CONSUME:

Various 0,150 - 0,250 Lt /m².

PACKING:

15,00 kg. Bin

100x100 Pallet Dimension

36 Qty on Pallet

COLOR:

White

SHELF LIFE:

1 year from the production date under proper storage conditions.

Close tight the opened bags.

SAFETY RECOMMENDATIONS:

Wear work clothes, protective gloves, glasses and masks should be used during application.

As it cement based, do not breath and do not touch with skin and eyes,

Due to the irritating effects of the cured materials, skin and eyes should not be contacted, in case of contact with wash plenty of water and soap, if swallowed seek medical attention immediately.

Food and beverage materials should not be kept in the application area and should not be eaten.

Store out of reach of children.

This product packaging must be disposed of in accordance with applicable laws.

This responsibility is belong the end user.

For more information please check the Material Safety Data Sheet.

LIMITATIONS OF LIABILITY:

The information in this technical data sheet is given according to technical information, experience and test result.

As GENERALTÜRK A.Ş. cannot control the usage of the product that used under which



D-THERM 556

It is a water based, acrylic emulsion based exterior primer.

kind of conditions, it does not accept any responsibility for the application result and does not guarantee it.

The product suitability for the product user should be tested and decided accordingly.

All products should be considered in the advice of those technical knowledge and equipment.

GENERAL TURK A.Ş can not accept any responsibility that occurs because of misuse, it only responsible for the written suggestions that shows the products where and how use.

GENERALTÜRK A.Ş. It may change the properties of its products without announcement.

The technical data sheet is valid until the next time it is printed and all previous technical data sheets invalidate the description / January 2020