

LIME-C 504

It is a plaster and screed plasticizer additive that used in production of the plaster and screed instead of the lime.

DESCRIPTION:

It is a plaster and screed plasticizer additive that used in production of the plaster and screed instead of the lime.

ADVANTAGES:

Low cost
Labor cost is low.
Ready for use.
Used during concrete pouring.
Provides high quality mortar.
Increase the workability.
As the necessity of the water decrease while using this product the durability.

USAGE AREAS:

Can be used instead of lime in cement-based mortar.
Indoor and Outdoor plaster production.
Walling of the brick and wall mortar.
Production of the screed.

TECHNICAL SPESIFICATION: (23 °C

Heat and %50 Relative Humidity)

Color : White-Transparent

Density : 20°C : 1,1 gr/cm3

APPLICATION METHOD:

Application:

The necessary water poured into a clean bucket, the mortar that going to be prepared should be dosed between %0,1 to % 0,5 according to mortar type, lastly mix with mortar water.

Make the mortar with the prepared water.

The product must be put in to mixed water, do not add directly to mortar.

ISSUES TO BE CONSIDERED:

Temperature should be between +5 °C and +35 °C during the application.

Do not apply on surfaces that are at risk of frost.

In addition, it should not be applied in extremely hot, rainy or windy weather.

This time can change according to temperature and moist ratio.

CLEANING OF INSTRUMENTS:

DAYMAN LIME C –504 should be cleaned by water just after the application.



LIME-C 504

It is a plaster and screed plasticizer additive that used in production of the plaster and screed instead of the lime.

CONSUME:

% 0,1 to % 0,5 of the total cement percentage.

In order to catch the best dose and result, the result of the test must checked.

PACKING:

30, 00 kg. Bin.

80x120 Pallet Dimension

Qty.on Pallet 24

5, 00 kg. Bin.

80x120 Pallet Dimension

Qty.on Pallet 120

COLOR:

White-Transparent

SHELF LIFE:

1 year from the production date under proper storage conditions.

Opened packages should be kept tightly closed.

Wear work clothes, protective gloves, glasses and masks should be used during application.

SAFETY RECOMMENDATIONS:

Skin and eyes should not be contacted, in case of contact with wash plenty of water and soap, if swallowed seek medical attention immediately.

Food and beverage materials should not be kept in the application area and should not be eaten.

Store out of reach of children.

This product packaging must be disposed of in accordance with applicable laws.

This responsibility is belong the end user.

For more information please check the Material Safety Data Sheet.

LIMITATIONS OF LIABILITY:

The information in this technical data sheet is given according to technical information, experience and test result.

As GENERALTÜRK A.Ş. cannot control the usage of the product that used under which kind of conditions, it does not accept any responsibility for the application result and does not guarantee it.

The product suitability for the product user should be tested and decided accordingly.



LIME-C 504

It is a plaster and screed plasticizer additive that used in production of the plaster and screed instead of the lime.

All products should be considered in the advice of those technical knowledge and equipment.

GENERAL TURK A.Ş can not accept any responsibility that occurs because of miss-use, it only responsible for the written suggestions that shows the products where and how use.

GENERALTÜRK A.Ş. It may change the properties of its products without announcement.

The technical data sheet is valid until the next time it is printed and all previous technical data sheets invalidate the description / January 2020

CE 2765	
GENERALTURK TEKNİK YALITIM KİMYA END. SAN. TİC. A.Ş. YUNUSELİ MH. 15. YAVUZ SK. NO: 21 OSMANGAZİ - BURSA / TÜRKİYE 20	
2765 - CPR - 0156 EN 934 - 2	
LIME-C 504	
CONCRETE ADMIXTURES	
Intended use in concrete for water resisting;	
Colour	White-Transparent
Density 20°C	20°C 1,1 gr/cm3