



D-THERM – 559

Alkali-resistant, mesh corner profile for jacketing applications

DESCRIPTION:

Alkali-resistant, mesh corner profile for jacketing applications.

ADVANTAGES:

It provides smooth corner lines in sheathing application.

It is alkali resistant.

It is resistant to temperature changes.

It is easy to apply.

USAGE AREAS:

It is used in the application of the DAYMAN D-THERM 552

TECHNICAL SPESIFICATION :

(23 °C Temperatur and 50 % for relative humidity)

Dimension: 2,50 mt.height

***These values were obtained as a result of laboratory tests, just contain finished applications according to drying time performance. Due to differences in temperature and humidity values in the construction site, the values may change.

APPLICATION METHOD:

Surface Preparation:

It should be cut and prepared according to place that going to be used in application.

It should be overlapped 100 cm at the joints with DAYMAN D-TEX 160.

DAYMAN D-THERM 552 is embedded in the D-THERM 559 product when it is wet after 1 coat is applied.

After it become dry the second layer should be done with DAYMAN D-THERM 552.

CONSUME:

Various 0,25 mt/m².

PACKING:

62,50 mt

COLOR:

Orange

SHELF LIFE:

Should be stored upright.

Protect from direct sunlight.



D-THERM – 559

Alkali-resistant, mesh corner profile for jacketing applications

LIMITATIONS OF LIABILITY:

The information in this technical data sheet is given according to technical information, experience and test result.

As GENERALTÜRK A.Ş. cannot control the usage of the product that used under which kind of conditions, it does not accept any responsibility for the application result and does not guarantee it.

The product suitability for the product user should be tested and decided accordingly.

All products should be considered in the advice of those technical knowledge and equipment.

GENERAL TURK A.Ş can not accept any responsibility that occurs because of miss-use, it only responsible for the written suggestions that shows the products where and how use.

GENERALTÜRK A.Ş. It may change the properties of its products without announcement.

The technical data sheet is valid until the next time it is printed and all previous technical data sheets invalidate the description / January 2020