



ST PRIMER – 619

Exposed Concrete Primer

DESCRIPTION:

Water based, acrylic emulsion based, exposed concrete primer.

ADVANTAGES:

It increase adherence of the plaster that is applied on the concrete.

Increases especially the processing time gypsum plaster and cement.

Easy to apply.

Prevents rapid water loss of plasters.

USAGE AREAS:

Before plaster

Before cement based plaster

Horizontal and vertical surfaces

TECHNICAL SPESIFICATION :

(23 °C Temperature and 50 % for relative humidity)

Application Temperature : +5 - +30 °C

Waste : 0,200 Kg/m²

Color : White-After drying transparent

Drying Time : 1-2 hour

Doing Plaster On : 24 hours

***These values were obtained as a result of laboratory tests, just contain finished applications according to drying time

performance. Due to differences in temperature and humidity values in the construction site, the values may change.

APPLICATION METHOD:

Surface Preparation:

The surface; must be cured, dry and durable. Loose surface mortar and such as residues should be cleaned and reached durable surface.

In case of the necessity the surface should cleaned mechanically.

Oil, grease, dirt, paint, salt and vomiting that prevent adhesion should be removed.

Preparation Of The Mixture:

ST PRIMER 619 is ready for use – can be added 4-6 lit. water.

Application:

ST PRIMER 619 can be applied by roller, brush and suitable spraying equipment.

It should be mixed occasionally during application.

ISSUES TO BE CONSIDERED:

Temperature should be between +5 °C and +35 °C during the application.

Do not apply on surfaces that are at risk of frost.



ST PRIMER – 619

Exposed Concrete Primer

The product should be protected from rain, water, frost and negative external factors until curing.

After the application should prevent from direct contact with water the first 24 hours.

CLEANING OF INSTRUMENTS:

DAYMAN ST PRIMER – 619 should be cleaned by water when it wet.

DAYMAN ST PRIMER – 619 after become dry should be cleaned by the mechanical ways.

CONSUME:

0,200 kg / m².

PACKING:

12 kg.Bin

COLOR:

Blue

SHELF LIFE:

1 year from the production date under proper storage conditions.

The opened pack should be closed tightly.

SAFETY RECOMMENDATIONS:

Wear suitable protective clothing, protective gloves, goggles and mask during application.

Hands and eyes must be protected with gloves and protective glasses. In case of contact with material, wash eyes with plenty of water rinse and consult a doctor immediately.

No food or beverage should be allowed in the application area.

Store out of reach of children.

This product packaging must be disposed of in accordance with applicable laws.

This responsibility is belong the end user.

For more information please check the Material Safety Data Sheet.

LIMITATIONS OF LIABILITY:

The information in this technical data sheet is given according to technical information, experience and test result.

As GENERALTÜRK A.Ş. cannot control the usage of the product that used under which kind of conditions, it does not accept any responsibility for the application result and does not guarantee it.



ST PRIMER – 619

Exposed Concrete Primer

The product suitability for the product user should be tested and decided accordingly. All products should be considered in the advice of those technical knowledge and equipment.

GENERAL TURK A.Ş can not accept any responsibility that occurs because of miss-use, it only responsible for the written suggestions that shows the products where and how use.

GENERALTÜRK A.Ş. It may change the properties of its products without announcement.

The technical data sheet is valid until the next time it is printed and all previous technical data sheets invalidate the description / January 2020