

LEVEL PR- 617

Bond Coat for Cement Based Screeds

DESCRIPTION:

It is a mortar bond coat primer used under cement based screeds and layers.

ADVANTAGES:

Form a strong bond between old concrete and screed.

Water impermeable.

Resistant to frost.

Suitable for internal and external use.

USAGE AREAS:

Horizontal and vertical surfaces.

Indoor and outdoor areas.

Before screed casting.

Before the use of repair mortar

APPLICATION METHOD:

Surface Preparation:

The surface; must be cured, dry and durable. Loose surface mortar and such as residues should be cleaned and reached durable surface.

The hole diameter should be 4 mm bigger than the pin diameter that to be anchored.

The hole depth should be roughly 15 times the hole diameter.

The holes should be cleaned with a brush or compressed air so that no dust, oil, foreign matter remains.

Preparation Of The Mixture:

Dayman Level PR is ready for use.

Application:

The product is applied to the floor with a brush.

It should be covered with screed or cement based product before not become completely dry.

ISSUES TO BE CONSIDERED:

Temperature should be between +5 °C and +35 °C during the application.

Do not apply on surfaces that are at risk of frost.

The product should be protected from rain, water, frost and negative external factors until curing.

After the application should prevent from direct contact with water the first 24 hours.

CLEANING OF INSTRUMENTS:

DAYMAN LEVEL PR – 617 should be cleaned by water when it wet.



LEVEL PR- 617

Bond Coat for Cement Based Screeds

DAYMAN LEVEL PR - 617 after become dry should be cleaned by the mechanical ways.

CONSUME:

Various 0,150 - 0,300 kg/m².

PACKING:

30 kg.

COLOR:

Light Blue.

SHELF LIFE:

1 year from the production date under proper storage conditions.

The opened pack should be closed tightly.

SAFETY RECOMMENDATIONS:

Wear work clothes, protective gloves, glasses and masks should be used during application.

As it is cement based do not swallow the powder.

Due to the irritating effects of the cured materials, skin and eyes should not be contacted, in case of contact with wash

plenty of water and soap, if swallowed seek medical attention immediately.

Food and beverage materials should not be kept in the application area and should not be eaten.

Store out of reach of children.

This product packaging must be disposed of in accordance with applicable laws.

This responsibility is belong the end user.

For more information please check the Material Safety Data Sheet.

LIMITATIONS OF LIABILITY:

The information in this technical data sheet is given according to technical information, experience and test result.

As GENERALTÜRK A.Ş. cannot control the usage of the product that used under which kind of conditions, it does not accept any responsibility for the application result and does not guarantee it.

The product suitability for the product user should be tested and decided accordingly.

All products should be considered in the advice of those technical knowledge and equipment.

GENERAL TURK A.Ş can not accept any responsibility that occurs because of miss-



LEVEL PR- 617

Bond Coat for Cement Based Screeds

use, it is only responsible for the written suggestions that show the products where and how to use.

GENERAL TÜRK A.Ş. It may change the properties of its products without announcement.

The technical data sheet is valid until the next time it is printed and all previous technical data sheets invalidate the description / January 2020